

## NorTorque model 340, 1/2", Adjustable Ratchet (Dual Scale)



The NorTorque® utilises Norbar's proven mechanism and internal components and incorporates them into a purposeful and attractive torque wrench

In developing NorTorque®, Norbar's objective was to deliver outstanding quality and performance in a value for money package. Fine engineering ensures that the wrench adjustment is both fast and fingertip light meaning that you can do your job more efficiently.

Supplied with a Declaration of Conformance which meets the requirements ISO 6789-1:2017

Accurate to  $\pm 3\%$  of reading with models available to cover 12 N·m to 340 N·m.

**Part number:** 130106

**EAN Bar Code:** 5060207565387

**NATO number:** 5120-99-6908519

**Accuracy:**  $\pm 3\%$

**Operates between:**

60.00 - 340.00 N·m

45.00 - 250.00 lbf·ft



## TECHNICAL SPECIFICATIONS

- Length: 679mm
- Weight: 1.55kg
- Ratchet Teeth: 60
- Square Drive: 1/2"
- Ratchet Diameter: 52mm
- Scale Increments (N·m): 2
- Scale Increments (lbf·ft): 10

## FEATURES

- Convenient hanger feature for tool storage also aids wrench unlocking and adjustment
- Just eight turns to cover the entire scale
- Micrometer scale applying to the primary torque units (N·m on a dual scale wrench) for simple and error free setting
- Push/pull lock is fast and intuitive to use and prevents accidental adjustment of the set torque
- Light and fast adjustment saves operator time and effort
- Push through ratchets with a narrow engagement angle of 6° for working in tight space
- Supplied with a Declaration of Conformance, which meets the requirements of ISO 6789-1:2017

## DIMENSIONS & WEIGHT

**Tool Weight:** 1.49


**Packed Weight:** 2.06

**Dimensions:** 700 x 30 x 30

**Packed Length:** 732.00

**Packed Height:** 72.00

**Packed Width:** 82.00



---

NORBAR TORQUE TOOLS LTD. Wildmere Road, Banbury, Oxfordshire,  
OX16 3JU, United Kingdom  
Registered Office as above - Registered in England No. 380480 - VAT No.  
GB 119 1060 05

- Tel: + 44 (0) 1295 270333
- Enquiries: + 44 (0) 1295 753600
- After Sales : + 44 (0) 1295 753635
- Fax: + 44 (0) 1295 753609
- Email: [enquiry@norbar.com](mailto:enquiry@norbar.com)
- Repairs: [repairs@norbar.com](mailto:repairs@norbar.com)