

HONEYWELL BW™ FLEX



Multi-Gas Detector

With a choice of 12 different sensor types, the BW™ Flex protects you from multiple gas hazards, in a small, rugged, and easy to use device. BW™ Flex keeps specialists operating in confined spaces, or general workers on a plant, safe from gas hazards while making safety compliance for the business easy.

WORK THE WAY YOU WANT TO

The IntelliFlash™ and ultra-bright alarm LEDs provide users an instant overview of the detectors status. Red for stop, amber as a warning, and green you're good to go, gives that simple view inexperienced users need. The display can also be configured to show all the gases at the same time or one at a time. Either way the operator gets all they need to know at a glance.

MORE GASES FOR MORE APPLICATIONS

Select up to 4 sensors from 12 different gas types. With common gases covered and a growing range of "exotic" sensors too, the BW™ Flex can be used to protect workers in even more industries.

READY FOR THE CONNECTED FUTURE

Pairing the BW™ Flex with your smart mobile device via Bluetooth™ allows remote measurement, field reporting of incidents, or even full instrument configuration and calibration. What's more everything is recorded for download when needed.



For the detection of the most common gas hazards including: Flammable gas (LEL), oxygen (O₂), carbon monoxide (CO), hydrogen sulphide (H₂S), carbon dioxide (CO₂), sulphur dioxide (SO₂), chlorine (Cl₂), nitric oxide (NO), nitrogen dioxide (NO₂), and hydrogen cyanide (HCN)

FEATURES AND BENEFITS



RELIABLE

Small, lightweight, rugged, and weatherproof, the BW™ Flex can be used in potentially explosive atmospheres. Indoor, outdoor, onshore or offshore, we have you covered globally.



STATUS AT A GLANCE

The IntelliFlash™ status indicator enables quick visual compliance status checks in the field using an intuitive green, amber and red color coding.



ADVANCED CONNECTIVITY

Using a smart mobile device or PC operators can fully configure their device using Safety Suite solutions on iOS®, Android™, or Windows™ platforms. Safety Communicator allows full remote situational awareness from the control room when needed.



RESPONSIVE

Offering instantaneous alarms, with time weighted average exposure levels (STEL/ TWA), users are protected all round, from flammable, oxygen, and toxic gases in the work place.



EASY TO MAINTAIN

The modular design makes service and maintenance easy. Compatibility with IntelliDoX automated test and calibration system, makes the routine fast! The system ensures up to date records are always available.



EASY TO USE

The single pushbutton operation, intuitive user interface, and simple green/amber/red alarm system simplifies training and enables users to be up and running quickly.

Honeywell

Honeywell BW™ Flex Series Technical Specifications

| Sensor Specifications | | | | | | | | | | | | | |
|------------------------------|---|--------------------------|---|---|---------------------------|---------------------------|----------------------------|----------------------------|---------------------------|---------------------------|--------------------------|---------------------------|--------------------------|
| Gas Type | LEL-IR | NDIR-CO2 | LEL-CB-F | LEL-CB-UF | O2 | H2S | CO | CO-H | SO2 | NO | NO2 | HCN | CL2 |
| Identifier | W5 | B1 | W6 | W7 | X1 | H1 | M1 | M3 | S3 | N3 | D3 | Z3 | C3 |
| Spare Sensor | SR-W5-1S | SR-B1-1S | SR-W6-1S | SR-W7-1S | SR-X1-1S | SR-H1-1S | SR-M1-1S | SR-M3-1S | SR-S3-1S | SR-N3-1S | SR-D3-1S | SR-Z3-1S | SR-C3-1S |
| Type | NDIR C1-C6 Hydrocarbons | NDIR CO2 | Cat. Bead Filtered | Cat. Bead Unfiltered | Pb free Electrochem. | Electrochemical | Electrochemical | Electrochemical | Electrochemical | Electrochemical | Electrochemical | Electrochemical | Electrochemical |
| Interface | Digital | Digital | Digital | Digital | Bias O2 Pump | Inflow | Inflow | Inflow | Inflow | Bias | Outflow | Inflow | Outflow |
| Operating Temperature | -20°C/60°C -4°F/140°F | -20°C/60°C -4°F/140°F | -20°C/60°C -4°F/140°F | -20°C/60°C -4°F/140°F | -40°C/60°C -40°F/140°F | -40°C/60°C -40°F/140°F | -40°C/60°C -40°F/140°F | -20°C/50°C -4°F/122°F | -20°C/50°C -4°F/122°F | -20°C/50°C -4°F/122°F | -20°C/50°C -4°F/122°F | -10°C/50°C 14°F/122°F | -20°C/50°C -4°F/122°F |
| Recommended Operating Range | 100% LEL | 5% VOL (50000 ppm) | 100% LEL | 100% LEL | 25% VOL | 200 ppm | 1000 ppm | 1000 ppm | 20 ppm | 100 ppm | 20 ppm | 50 ppm | 20 ppm |
| Maximum Over Range | 100% LEL | 5% VOL (50000 ppm) | 100% LEL | 100% LEL | 30% VOL | 500 ppm | 2000 ppm | 2000 ppm | 150 ppm | 400 ppm | 60 ppm | 250 ppm | 60 ppm |
| Resolution | 1% LEL | 0.1% VOL (100 ppm) | 1% LEL | 1% LEL | 0.1% VOL | 0.1 ppm | 1 ppm | 1 ppm | 0.1 ppm | 0.1 ppm | 0.1 ppm | <0.3 ppm | 0.1 ppm |
| Default Units of Measure | % LEL | % VOL | % LEL | % LEL | % VOL | ppm | ppm | ppm | ppm | ppm | ppm | ppm | ppm |
| Configurable Alarm Range | 0 (disable) to 100% LEL | 0 (disable) to 5% VOL | 0 (disable) to 100% LEL | 0 (disable) to 100% LEL | 0 (disable) to 30% VOL | 0 (disable) to 200 ppm | 0 (disable) to 2000 ppm | 0 (disable) to 2000 ppm | 0 (disable) to 150 ppm | 0 (disable) to 400 ppm | 0 (disable) to 60 ppm | 0 (disable) to 250 ppm | 0 (disable) to 60 ppm |
| Default Low Alarm | 10% LEL | 0.5% VOL (5000 ppm) | 10% LEL | 10% LEL | 19.5% VOL | 10 ppm | 35 ppm | 35 ppm | 2 ppm | 25 ppm | 2 ppm | 4.7 ppm | 0.5 ppm |
| Default High Alarm | 20% LEL | 3.0% VOL (30,000 ppm) | 20% LEL | 20% LEL | 23.5% VOL | 15 ppm | 200 ppm | 200 ppm | 5 ppm | 25 ppm | 5 ppm | 10 ppm | 1 ppm |
| Default STEL | n/a | 3.0% VOL (30,000 ppm) | n/a | n/a | n/a | 15 ppm | 50 ppm | 50 ppm | 1 ppm | 25 ppm | 5 ppm | 10 ppm | 1 ppm |
| Default TWA | n/a | 0.5% VOL (5000 ppm) | n/a | n/a | n/a | 10 ppm | 35 ppm | 35 ppm | 0.5ppm | 25 ppm | TBC | TBC | 0.5 ppm |
| Default Span Gas | 50% LEL CH ₄ (2.2/2.5% VOL) | 0.5% VOL (5000 ppm) | 50% LEL CH ₄ (2.2/2.5% VOL) | 50% LEL CH ₄ (2.2/2.5% VOL) | 18% VOL | 25 ppm | 100 ppm | 100 ppm | 20 ppm | 50 ppm | 10 ppm | 15ppm | 10 ppm |
| Maximum Calibration Interval | 180 days | 180 days | 180 days | 180 days | 180 days | 180 days | 180 days | 180 days | 180 days | 180 days | 180 days | 90 days | 180 days |
| Expected Operating Life | 3 to 5+ years | 3 to 5+ years | 3 to 5+ years | 3 to 5+ years | 3 to 5+ years | 3 to 5+ years | 3 to 5+ years | 2+ years | 3 to 5+ years | 2+ years | 2+ years | 1 to 2 years | 1 to 2 years |

Honeywell BW™ Flex Series Technical Specifications

| Technical Specifications | |
|---|--|
| Size | 108.2 mm × 61.5 mm × 43.2 mm (4.29 in × 2.44 in × 1.7 in) with Alligator Clip 108.2 mm × 61.5 mm × 37.8 mm (4.29 in × 2.44 in × 1.49 in) with Klick Fast Stud |
| Weight | With Catalytic LEL: 189 g (6.7 oz) with Alligator Clip, 173 g (6.1 oz) with Klick Fast Stud With IR LEL: 186 g (6.6 oz) with Alligator Clip, 170 g (6.0 oz) with Klick Fast Stud |
| Certified Temperature | -40°C to 60°C (-40°F to 140°F) and -20°C to 60°C (-4°F to 140°F) with Catalytic LEL sensor |
| Working Humidity | 5% to 95% rH (non condensing) |
| Ingress Protection | IP66, IP68 |
| Alarms and Type | Visual, vibrating, audible (95 dB); Low, High, TWA, STEL, Negative Drift, Over Limit, Multi-alarm, Low Battery |
| Self-Test | Perform diagnostic of sensor, circuitry on activation; Reflex™ test automatically performs analog sensor diagnostic every 10 minutes |
| Typical Battery Life* | 40 days @ 8 hours of use per day with IR LEL, up to 15 hour with Catalytic LEL (with NDIR CH ₄ sensor) |
| Connected Worker | Bluetooth® Low Energy (BLE) – Ability to connect to Honeywell's Safety Communicator App, Device Configurator App and Safety Suite Device Configurator Software |
| User Options (Changed using Safety Suite and/or Device Configurator App) | <ul style="list-style-type: none">• Change High, Low, TWA, and STEL alarm set points• Latching alarms• Set calibration and/or bump test reminders, apply enforcement policies• Assign worker and location assignments• Always on |
| Certifications and Approvals | ATEX, IEC Ex, contains FCCID, contains IC, CSA Suitable for use in potentially explosive atmospheres found in industrial, marine, and mining applications. Contact Honeywell for the latest list of global approvals |

*depends on alarm duration.



Caution: The infrared LEL sensor used in Honeywell BW™ Flex cannot detect hydrogen and acetylene. For applications involving these combustible gases, please specify the catalytic type LEL sensor.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship during the applicable warranty period. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgment or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items that Honeywell, in its sole discretion, finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While Honeywell may provide application assistance personally, through our literature and the Honeywell web site, it is buyer's sole responsibility to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate as of this writing. However, Honeywell assumes no responsibility for its use.



Territory Instruments
A: 15 Raphael Road, Winnellie, NT, 0820
T: +61 8 8947 5450
E: info@territoryinstruments.com
W: www.territoryinstruments.com

Bluetooth is a trademark or registered trademark of Bluetooth SIG, Inc.
Android is a trademark or registered trademark of Google LLC.
Windows is a trademark or registered trademark of Microsoft Corporation.
iOS is a trademark or registered trademark of Cisco
Honeywell BW™ is a trademark or registered trademark of Honeywell International Inc.

GAS_BW_Flex Series_DS | Rev C | 04/24
© 2024 Honeywell International Inc.

Honeywell